

SOLACE zero clearance direct vent gas fireplace

Unit Illustrated: Solace HBZDV4736N Direct Vent Fireplace, LOGF36 Fiber Split Oak Log Set, VLBI74 Log Bits, HB47CVCK Designer Clean View Circulating Kit, HB47RRH Red Herringbone Brick Liner.



SOLACE SPECIFICATIONS

SOLACE	Model Flue Fuel Input Max. Input Min. FE (P.4.1-15) Log Set	MQHBZDV3636N/NE MQHBZDV4236N/NE Top Natural Gas 30,500 BTU 29,000 BTU 61.98% / 63.92% LOGF36	MQHBZDV3636LP/LPE MQHBZDV4236LP/LPE Top Propane 29,000 BTU 22,200 BTU 67.63% / 69.25% LOGF36	HBZDV4736N HBZDV4736NE Top Natural Gas 40,000 BTU 27,000 BTU 60.39% / 61.88% LOGF36	HBZDV4736LP HBZDV4736LPE Top Propane 36,000 BTU 30,000 BTU 53.79% / 54.90% LOGF36
SOLACE II	Model Flue Fuel Input Max. Input Min. FE (P.4.1-15) Log Sets	HBZDV3624N/NE Top Natural Gas 24,00 BTU 14,000 BTU 50,48% / 52.30% MQLOGC45 LOGC44	HBZDV3624LP/LPE Top Propane 22,000 BTU 15,000 BTU 52.59% / 54.24% MQLOGC45 LOGC44	HBZDV4224N/NE Top Natural Gas 24,000 BTU 14,000 BTU 55.69% / 57.81% MQLOGC45 LOGC44	HBZDV4224LP/LPE Top Propane 22,000 BTU 15,000 BTU 57.03% / 59.09% MQLOGC45 LOGC44

TOP FLUE	Hei	ght	Front	Width	De	Depth			
MODEL	Actual	Framing	Actual	Framing	Actual	Framing			
LOUVERS									
HBZDV36	34 ¹³ ⁄16"	35"	36"	36 3⁄8"	16 7⁄16"	17"			
HBZDV42	37"	37 ¾"	41 1/8"	42 ¾"	16 7⁄16"	17"			
HBZDV47	43 1⁄16"	43 1⁄8"	47 ¼16"	47 ³ /8"	19 7⁄16"	19 ½"			
CLEAN VIEW CIRCULATING KIT									
HBZDV36	34 11/16"	41"	38 1⁄16"	38 7/16"	18 1/8"	19 ½"			
HBZDV42	36 ¹³ ⁄16"	43"	42 ¼16"	42 1/16"	18 ¹⁵ /16"	19 ½"			
HBZDV47	49"	49 ½"	48 1/16"	48 ¾"	21 ¹⁵ /16"	22"			

K → A →

CORNER FRAMING DIMENSIONS (INCHES): LOUVERED UNITS					CORNER FRAMING DIMENSIONS (INCHES): CLEAN VIEW CIRCULATING KIT (CVK)						
HBZDV36		HBZDV42		HBZDV47		HBZDV36		HBZDV42		HBZDV47	
Α	54 ¹³ ⁄16"	Α	58 ¹³ /16"	Α	65 ¼"	Α	59 ¾"	Α	63 ¹³ /16"	Α	70 ³ /16"
В	36 3⁄8"	В	42 ³ /8"	В	47 ³ /8"	В	38 7⁄16"	В	42 1/16"	В	48 ¾"
С	36"	С	41 1⁄8"	С	47 1⁄16"	С	38 1⁄6"	С	42 1/16"	С	48 1⁄16"
D	9 ³ /16"	D	8 ¼"	D	8 ¹⁵ / ₁₆ "	D	10 ¹¹ / ₁₆ "	D	10 11/16"	D	10 1⁄8"
Е	38 ¾"	Е	41 5⁄8"	Е	46 1/8"	Е	42 5/16"	Е	45 1⁄8"	Е	49 5⁄8"
F	12 3⁄8"	F	13 ³ ⁄4"	F	13 ¹⁵ /16"	F	12 3⁄8"	F	13 ¾"	F	13 ¹⁵ /16"
G	17 %16"	G	19 ½"	G	19 ¹¹ / ₁₆ "	G	17 %16"	G	19 ½"	G	19 ¹¹ / ₁₆ "
н	27 3⁄8"	н	29 7⁄16"	н	32 5⁄8"	Н	29 5/16"	н	31 1/8"	н	35 1⁄16"



Unit Illustrated: Solace II HBZDV4224N Direct Vent Fireplace, MQLOGC45 Oak Log Set, HB42GBL Grill Kit (Black), HB42RLT Traditional Brick Liner.



Unit Illustrated: Solace II HBZDV3624N Direct Vent Fireplace MQLOGC45 Oak Log Set, HB36CVCK Designer Clean View Circulating Kit, HB36RLH Herringbone Brick Liner.





TOP FLUE MODEL VIEWING AREA

Height

18 5⁄8"

20 3⁄8"

Width

HBZDV36 29 3/4"

HBZDV42 33 3/8"

HBZDV47 39 1/2"

FIND YOUR SOLACE

SOLACE ACCESSORIES

Imagine lively gatherings or times of quiet reflection in front of the beautiful **Solace**. Available in two sizes, the **Solace** allows you to transform your fireplace into something truly unique.

With so much style and attention to detail, the **Solace** is available in a range of sizes and styles. You can choose from our mid-efficient rated fireplace for ambiance and taking the chill out of the room, or our higher-efficient version for additional warmth.

LOG SETS





LOGF36 Fibre Split Oak (SOLACE)

ROCK SETS

MQLOGC45 Burnt Oak (SOLACE II)



LOGC44 (SOLACE II)

LINER

STANDARD FEATURES

- Millivolt or IPI valve system allows operation during a power failure with Hi/Low heat and flame adjustment
- Dual burner with Realistic Flame Pattern
- Safety Screen Barrier

OPTIONAL FEATURES

Designer Clean View Circulating Kit: No Louvers Required

Louvers: Grills available in Black

Fan Kit: Heat activated with variable speed control

Accessories: Log sets or rock sets required

Liners: Porcelain Reflective Liner or Brick Liners

Thermostat: Wall Mount or Programmable

Remote:

Thermostat On/Off, Thermostat On/Off modulating, Thermostat On/Off modulating and fan control



REQUIRES SUPPORT PLATFORM (SOLACE I ONLY)



MQROCK2 Multi-Colored Rock Set

PL Porcelain Reflective

BRICK LINERS

MQROCK2 Natural Rock Set





RLH Herringbone Brick

RRH Red Herringbone Brick



RLT Traditional Brick

See the latest evolution in fireplaces at marquisfireplaces.net



80 --

F1 IPI/MV





Marquis Fireplaces maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.

Certified to: ANSI Z21.88-2017 • CSA 2.33-2017 Vented Gas Fireplace Heaters, CSA 2.17-2017

Note: Components may have to be ordered separately to create a complete unit. Discuss with your local Marquis Dealer for clarification.

Look for the **EnerGuide** Gas Fireplace Energy Efficiency Rating in this brochure

Based on CSA P.4.1-15

FOR CALIFORNIA RESIDENTS ONLY:

WARNING! This product can expose you to chemicals including Carbon Monoxide, that is an externally vented by-product of fuel consumption, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information, visit www.P65Warnings.ca.gov. Crafted entirely in Canada, each Marquis fireplace is built to the highest standards and made to last.

LIMITED LIFETIME WARRANTY



2340 Logan Avenue Winnipeg, Manitoba, CAN R2R 2V3 Phone: 204.632.1962 Fax: 204.632.1960 marquisfireplaces.net

Printed in Canada **B057 – 04/2023**